

SPRIT 雅各科技股份有限公司

SPIRIT INNOTECH INC.

No.10, Luke 1st Rd., Kaohsiung Science Park-

Lujhu Dist., Kaohsiung City, Taiwan (R.O.C.)

高雄市路竹區路科一路 10 號 TEL : 886-7-6955588 FAX : 886-7-6955599

Website:www.spirit.tw.com

SPIRIT-213-ID UL CERTIFICATED PVC INSULATING TAPE

Applications

- Joining and marking for engineers.
- Automotive industry and auto aftermarket.
- Protection for delicate surfaces
- Temporary bundling.

● **Features**

- Excellent adhesion.
- Excellent weather resistance.
- Great elasticity.
- Various colors.

Physical

Property:	Backing	PVC Film
	Adhesive System	Rubber Solvent
	Total Thickness (mm)	0.18± 0.018
	Tensile Strength (kg / 25mm)	7 ↑
	Elongation (%)	180 ↑
	Adhesion to Stainless Steel (kg / 25mm)	0.450 ↑
	Dielectric Strength	7000 ↑

Size

Color :	Colors
Film Width (mm) :	1300mm
Coating Width (mm) :	1270mm

For more available sizes please contact our sales representatives

Note While we believe above information to be reliable, the statements and information herein are only for general guidance and are not warrants of guarantees for accuracy and completeness. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience.THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Our standard terms and condition of sales apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE ARE EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice in our products and publications. User is responsible for determining whether our product is fit for a particular purpose and suitable for user's application. If you are in any doubt, our technical support staff will be glad to advise you.

(2017/6/28 version)