

# **SPRIT 雅各科技股份有限公司**

**SPIRIT INNOTECH INC.**

No.10, Luke 1st Rd., Kaohsiung Science Park-

Lujhu Dist., Kaohsiung City, Taiwan (R.O.C.)

高雄市路竹區路科一路 10 號 TEL : 886-7-6955588 FAX : 886-7-6955599

Website:www.spirittw.com

## **SPIRIT-215-JG PVC PIPE WRAPPING TAPE**

### **Applications**

- General GENERAL INDUSTRIAL APPLICATIONS Bundling materials, duct sealing, strapping applications .
- BUILDING Maintaining, repairing, joining, sealing, masking or protecting many surfaces and materials

### ● **Features**

- Excellent uses to protect against corrosive chemicals.
- Water & solvent resistant.
- Available in a various sizes and bonds strengths.

### **Physical**

Property:Backing	PVC Film
Adhesive System	Rubber Solvent
Total Thickness ( mm )	0.200 ± 0.026
Tack (#)	20 ↑
Tensile Strength ( kg / 25mm )	6 ↑
Elongation ( % )	190 ↑
Adhesion to Stainless Steel ( kg / 25mm )	0.40 ↑

### **Size**

Color :	Black
Film Width (mm) :	1300mm
Coating Width (mm) :	1270mm

**For more available sizes please contact our sales representatives**

**Note** While we believe above information to be reliable, the statements and information herein are only for general guidance and are not warrants of guarantees for accuracy and completeness. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience.THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Our standard terms and condition of sales apply exclusively to all orders, and ALL LIABILITY FOR DAMAGES OF ANY KIND, INCLUDING CONSEQUENTIAL, EXCEEDING PURCHASE PRICE ARE EXCLUDED. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice in our products and publications. User is responsible for determining whether our product is fit for a particular purpose and suitable for user's application. If you are in any doubt, our technical support staff will be glad to advise you.

(2017/6/28 version)